



The Daikē Box Wrapper is a very good equipment for making high-grade rigid boxes, such as smart phone box, tablet PC box, Laptop box, shoe box, shirt box, underwear box, gift box, food box, tea box, wine box etc. Its speed is pretty good, more than 1500PCS per hour, even faster than automatic rigid box machine. Low cost, high speed. It is suitable for most of paper box packaging factory.

**Main Features:**

1. It adopts curved surface cam structure which makes the machine run more stably and with lower noise.
2. Automatically wrap, fold ear and paper sides, continually finishing the box in one process.
3. Multiple safety protection devices, safer and more human-friendly
4. Easy to change mold, suitable for different sizes of products
5. Brush rollers are drive by motor which make the wrapping more tightly and smoothly
6. Bottom mold adopts pneumatic structure, which effectively prevents the bubble.
7. Top mold has pressure detecting device. Machine does not start if top mold is without box or with the box which is not in place.
8. It is equipped with time-delay device to adjust the period from putting on box to (top mold) pushing down, which ensure the operation safety.
9. It adopts an innovative design 2 Servo drive shafts, integrated on one main shaft, run in same direction simultaneously when machine works which makes motions more coordinate and adjustment easier.
10. Whole components are processed by CNC machining equipment. One time positioning and processing, remove the positioning deviation, promote the precise and prolong the machine lifetime.

DAIKE - FCM 600



DAIKE - BWC 600



4 corner pressure synchronise system



Panasonic servo motor with delta drive system



Smooth flap brushing wheels for smooth finishing




Easy and quick adjustment and running with high quality pneumatic cylinders



Panasonic servo drive motor for accurate synchronization

**TECHNICAL DATA:**

Model	DAIKE - BWA600	DAIKE - BWM600	DAIKE - FCM600
Max overwrapping size	420 x 410 x 120 mm	460 x 400 x 100mm	520 x 420 x 150mm
Min overwrapping size	70 x 50 x 10 mm	100 x 80 x 15 mm	N/A
Power	2KW / 220V	1.1 KW / 380V	0.4KW / 380V
Air Pressure	0.4 - 0.6mpa	N/A	N/A
Size	1100 x 1050 x 3650mm	1100 x 1100 x 2350mm	800 x 700 x 800mm
Weight	980kg	600kg	400kg



Remarks: Specifications listed above are for refer only and be subjected to changes without any prior notice.